




7	8	REV	DESCRIPTION	APPD	DATE



- 1.额定功率/Rating:DC 12V 50mA;
2.接触阻抗/Contact Resistance:100mΩ Max;
3.绝缘/Insulation Resistance:100MΩ Max;
4.耐电压/Withstanding Voltage:AC250V For 1 Minute;
5.寿命/Life:30,000 cycles Min;
6.动作力/Operating Force:250±50gf;
7.行程/Travel:0.25±0.1mm;
8.使用温度/Operating Temperature:-20℃~70℃.

NO.	DESCRIPTION	QTY	MATERIAL	FINISH
1	STEM	1	PPA	WHITE
2	COVER	1	STEEL	PLATING CuSn
3	CONTACT	1	SUS	PLATING Ag
4	BOTTOM	1	PPA	WHITE
5	TERMINAL	2	BRASS	PLATING Ag
UNIT:MM		SIZE: A4	SHEET: 1 OF 1	TITLE: TACT SWITCH
		SCALE: /	VER: 1	MODEL NO: TS36A2-S50-V
PART NO:		DWG NO:		GONGQI ELECTRONIC CO.,LTD
GENERAL TOLERANCE:		DESIGNER BY:	YONGX	
X.=±0.25, .X=±0.2		APPROVED BY:	JACK	
.XX=±0.1, .XXX=±0.05		DATE:		
.X*=±2°, .XX*=±1°				